



Panasonic®

Headset Instructions

Model No. **WX-H3027**

Before attempting to connect or operate this product,
please read these instructions carefully and save this manual for future use.

No model number suffix is shown in this manual.

NWb0708-2108 3TR005573CBA Printed in China
Imprimé en Chine

ENGLISH VERSION

WARNING:

The risk of hearing impairment due to exposure to excessive sound levels may be reduced by listening at lower volumes and for shorter durations.

NOTE: Refer to the Operating Instructions of Order Taker for details on connection and so on.

■ Preface

Headset WX-H3027 is exclusively designed for use with Order Taker WX-C1020, WX-C920, WX-CT2020 and WX-T3020.

■ Precautions

- Do not use this product in the rain. When this product gets wet, wipe the product immediately with dry cloth, and dry the product sufficiently before use.
- Do not place this product under high temperatures such as near the heat sources or in the car with windows closed.

■ Limitation of Liability

THIS PUBLICATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THE THIRD PARTY'S RIGHT.

■ Disclaimer of Warranty

IN NO EVENT SHALL Panasonic Corporation BE LIABLE TO ANY PARTY OR ANY PERSON, EXCEPT FOR REPLACEMENT OR REASONABLE MAINTENANCE OF THE PRODUCT, FOR THE CASES, INCLUDING BUT NOT LIMITED TO BELOW:

- (1) ANY DAMAGE AND LOSS, INCLUDING WITHOUT LIMITATION, DIRECT OR INDIRECT, SPECIAL, CONSEQUENTIAL OR EXEMPLARY, ARISING OUT OF OR RELATING TO THE PRODUCT;
- (2) PERSONAL INJURY OR ANY DAMAGE CAUSED BY INAPPROPRIATE USE OR NEGLIGENT OPERATION OF THE USER;
- (3) UNAUTHORIZED DISASSEMBLE, REPAIR OR MODIFICATION OF THE PRODUCT BY THE USER;
- (4) ANY PROBLEM, CONSEQUENTIAL INCONVENIENCE, OR LOSS OR DAMAGE, ARISING OUT OF THE SYSTEM COMBINED BY THE DEVICES OF THIRD PARTY.

■ Specifications

Speaker Section

Type:	Dynamic
Impedance:	35 Ω at 1 kHz
Standard input:	10 mW
Maximum input:	40 mW
Output sound pressure level:	120 dB SPL at 1 kHz, 10 mW input
Frequency response:	150 Hz - 6 000 Hz

Microphone Section

Type:	Omnidirectional electret condenser microphone
Output impedance:	2.2 k Ω at 1 kHz
Sensitivity:	-44 dB at 1 kHz (0 dB = 1 V/Pa at 1 kHz)

Overall

Cord length:	1.1 m (3.6 ft.)
Weight:	95 g (0.21 lbs.)
Input/output plugs:	Combined ϕ 2.5/ ϕ 3.5 tip-ring type plug ϕ 2.5 plug: Microphone ϕ 3.5 plug: Speaker

Dimensions and weights indicated are approximate.
Specifications are subject to change without notice.